

BREEZE

TYPE:

Ceiling

PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



SHADE OPTIONS


ST = STANDARD BRM



MODEL - BREEZE PL 7

LIGHT SOURCE OPTIONS

H = HALOGEN - 7 x 10W 12V G4
or
L = LED - 7 x 1.5W 12V 2700K WW
100 Lumens each LED 30,000 hours



SPECIFICATION SHEET

HARCOLOOR DESIGN

DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.
LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

BREEZE

TYPE:

Ceiling

PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



SHADE OPTIONS


ST = STANDARD BRM



MODEL - BREEZE PL 9

LIGHT SOURCE OPTIONS


H = HALOGEN - 9 x 10W 12V G4
 or
 L = LED - 9 x 1.5W 12V 2700K WW
 100 Lumens each LED 30,000 hours



MODEL - BREEZE PL 12

LIGHT SOURCE OPTIONS


H = HALOGEN - 12 x 10W 12V G4
 or
 L = LED - 12 x 1.5W 12V 2700K WW
 100 Lumens each LED 30,000 hours



MODEL - BREEZE PL 15

LIGHT SOURCE OPTIONS

H = HALOGEN - 15 x 10W 12V G4
 or
 L = LED - 15 x 1.5W 12V 2700K WW
 100 Lumens each LED 30,000 hours



SPECIFICATION SHEET



DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.
 LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

BREEZE

TYPE:

Ceiling

PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



SHADE OPTIONS


ST = STANDARD BRM



MODEL - BREEZE PL 20

LIGHT SOURCE OPTIONS


H = HALOGEN - 20 x 10W 12V G4
 or
 L = LED - 20 x 1.5W 12V 2700K WW
 100 Lumens each LED 30,000 hours



MODEL - BREEZE PL 30

LIGHT SOURCE OPTIONS


H = HALOGEN - 30 x 5W 12V G4
 or
 L = LED - 30 x 1.5W 12V 2700K WW
 100 Lumens each LED 30,000 hours



MODEL - BREEZE PL 40

LIGHT SOURCE OPTIONS

H = HALOGEN - 40 x 5W 12V G4
 or
 L = LED - 40 x 1.5W 12V 2700K WW
 100 Lumens each LED 30,000 hours



SPECIFICATION SHEET



DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.
 LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.

BREEZE

TYPE:

Ceiling

PROJECT NAME:

MODEL #	SHADE COLOR	FIXTURE HEIGHT	HALO	LED	VOLTAGE
					120V



SHADE OPTIONS

ST = STANDARD BRM



MODEL - BREEZE PL 50


LIGHT SOURCE OPTIONS

H = HALOGEN - 50 x 5W 12V G4

or

L = LED - 50 x 1.5W 12V 2700K WW

100 Lumens each LED 30,000 hours



SPECIFICATION SHEET



DIMMING NOTE:

HALOGEN VERSION - Dimmable with a Low-Voltage Electronic dimmer.

LED VERSION - Dimmable with a leading edge or trailing edge TRIAC dimmer.